

Transducer-Class® Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition	GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSULATION OPTION AVAILABLE
	DIMENSIONS				

				Small dual-element gage designed for bending-beam transducers.			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH				
0.060	0.12	0.065	0.150	N2A-XX-S061P-350	350 ± 0.2%	P	E2
				N2K-XX-S085N-350/DP	350 ± 0.2%	N	E2
				N2K-XX-S098N-10C/DP	1000 ± 0.2%	N	E2
1.52	3.1	1.65	3.81	TK-XX-S085N-350/DP	350 ± 0.2%	N	E2
				TK-XX-S098N-10C/DP	1000 ± 0.2%	N	E2
MATRIX SIZE	0.19 L x 0.21 W	4.8 L x 5.3 W		SK-XX-S085N-350	350 ± 0.4%	N	


				Compact dual-element pattern for bending-beam transducers.			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH				
0.075	0.17	0.100	0.210				
1.90	4.2	2.54	5.33				
MATRIX SIZE	0.24 L x 0.25 W	6.1 L x 6.4 W		J2A-XX-S181N-350	350 ± 0.4%	N	
				J2A-XX-S185N-10C	1000 ± 0.4%	N	


				Half-bridge common-tab pattern. Grid centerline spacing 0.215 in (5.46 mm).			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH				
0.060	0.29	0.100	0.100				
1.52	7.4	2.54	2.54				
MATRIX SIZE	0.37 L x 0.16 W	9.3 L x 4.1 W		N2A-XX-S141K-175	175 ± 0.2%	K	E2
				N2A-XX-T028K-350	350 ± 0.2%	K	E2
				N2A-XX-S124N-10C	1000 ± 0.2%	N	E2


Note 1: Products shown in bold are not RoHS compliant.

Transducer-Class® Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition		GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSULATION OPTION AVAILABLE
	DIMENSIONS	<input type="checkbox"/> inch <input type="checkbox"/> millimeter				

				Half-bridge common-tab pattern. Grid centerline spacing 0.215 in (5.46mm).			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	N2K-XX-T011Q-350/DP TK-XX-T011Q-350/DP	350 ± 0.2% 350 ± 0.2%	Q Q	E2 E2
0.060	0.29	0.180	0.180				
1.52	7.4	4.57	4.57				
MATRIX SIZE	0.37 L x 0.24 W		9.3 L x 6.1 W				

				Half-bridge common-tab pattern. Grid centerline spacing 0.415 in (10.54mm). †BAL is balanced to ±0.2%, but RG is 350 ohms ± 15%.			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	N2A-XX-T012R-350 N2A-XX-S1414-35B N2K-XX-T016Q-350/DP TK-XX-T016Q-350/DP	350 ± 0.2% BAL ± 0.2%† 350 ± 0.2% 350 ± 0.2%	R N/A Q Q	E2 E2 E2 E2
0.060	0.49	0.100	0.100				
1.52	12.4	2.54	2.54				
MATRIX SIZE	0.57 L x 0.16 W		14.5 L x 4.1 W				


				Dual-element pattern for narrow bending beams. Grid centerline spacing 0.083 in (2.1mm).			
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH	N2A-XX-S1452-350 N2K-XX-S1451-350/DP TK-XX-S1451-350/DP	350 ± 0.2% 350 ± 0.2% 350 ± 0.2%	N/A N/A N/A	E2 E2 E2
0.062	0.233	0.062	0.062				
1.59	5.97	1.59	1.59				
MATRIX SIZE	0.28 L x 0.12 W		7.2 L x 3.1 W				


Note 1: Products shown in bold are not RoHS compliant.


Linear Patterns - Dual Grid

Transducer-Class® Strain Gages

GAGE PATTERN	Actual size shown. Enlarged when necessary for definition		GAGE DESIGNATION See Note 1	RES. IN OHMS	STANDARD CREEP CODE	ENCAPSULATION OPTION AVAILABLE
	DIMENSIONS	inch millimeter				

				Dual-element gages widely used on bending-beam transducers.		
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH			
0.125	0.20	0.065	0.150	N2A-XX-T006Q-350	350 ± 0.2%	Q
				J2A-XX-S035M-350	350 ± 0.4%	M
				N2K-XX-S082R-350/DP	350 ± 0.2%	R
				N2K-XX-T092P-10C/DP	1000 ± 0.2%	P
				TK-XX-S082R-350/DP	350 ± 0.2%	R
				TK-XX-T092P-10C/DP	1000 ± 0.2%	P
MATRIX SIZE	0.27 L x 0.21 W		6.9 L x 5.3 W			

				Wider-grid versions of T006/S035 patterns.		
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH			
0.125	0.21	0.100	0.220	N2A-XX-S138K-350	350 ± 0.2%	K
				N2A-XX-S139N-10C	1000 ± 0.2%	N
				J2A-XX-S138K-350	350 ± 0.4%	K
				J2A-XX-S139N-10C	1000 ± 0.4%	N
MATRIX SIZE	0.28 L x 0.28 W		7.1 L x 7.1 W			

				Widely used on bending-beam transducers where greater power dissipation is required. J2A pattern slightly longer and wider.		
GAGE LENGTH	OVERALL LENGTH	GRID WIDTH	OVERALL WIDTH			
0.250	0.34	0.100	0.215			
MATRIX SIZE	0.41 L x 0.28 W		10.4 L x 7.1 W			

Note 1: Products shown in bold are not RoHS compliant.

DISCLAIMER

All product specifications and data are subject to change without notice.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay Precision Group disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.